

Material Safety Data Sheet

Revision Issued: 2/26/2007

Supersedes: 2/26/2007

First Issued: 2/26/2007

Section I - Chemical Product And Company Identification

Product Name:

Desert Brand Master Seal Thick - Clear

CAS Number: N/A

HBCC MSDS No. CD04900



HILL BROTHERS Chemical Co.

1675 NORTH MAIN STREET • ORANGE, CALIFORNIA 92867-3499
(714) 998-8800 • FAX: (714) 998-6310
<http://hillbrothers.com>

1675 No. Main Street, Orange, California 92867

Telephone No: 714-998-8800 | Outside Calif: 800-821-7234 | Chemtrec: 800-424-9300

Section II - Composition/Information On Ingredients

Chemical Name	CAS Number	Exposure Limits (TWAs) in Air		
		ACGIH TLV	OSHA PEL	STEL
Methyl/Butyl Methacrylate Copolymer	28262-63-7	100 ppm	200 ppm	N/A
Ceramic Microspheres	66402-68-4	10 mg/m ³	15 mg/m ³	N/A
Aluminum Oxide	1344-28-1	10 mg/m ³	15 mg/m ³	N/A
Aromatic Hydrocarbon	1330-20-7	100 ppm	100 ppm	150 ppm
Aromatic Naphtha	64742-94-5	100 ppm	100 ppm	150 ppm

Section III - Hazard Identification

Summary of Acute Health Hazards N/A

Ingestion: Liquid ingestion may result in vomiting or abdominal pain.

Inhalation: High vapor/aerosol concentrations (greater than approximately 1000 ppm) are irritating to the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Negligible hazard at ambient temperature (-18 to 38°C; 0 to 100°F) and normal ventilation.

Skin: Prolonged and repeated liquid contact can cause drying of the skin which may result in skin irritation and dermatitis.

Eyes: May cause eye irritation on contact.

Summary of Chronic Health Hazards: N/A

Signs and Symptoms of Exposure: Prolonged or repeated skin contact with this product tends to remove oils possibly leading to irritation and dermatitis; however, based on

human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

Effects of Overexposure: High vapor concentrations (greater than approximately 1000 ppm) are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic, and may have other central nervous system effects.

Medical Conditions Generally Aggravated by Exposure: Skin contact may aggravate an existing dermatitis.

Note to Physicians: N/A

Section IV - First Aid Measures

Ingestion: If ingested, DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. GET MEDICAL ATTENTION IMMEDIATELY.

Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. GET MEDICAL ATTENTION IMMEDIATELY.

Skin: Wash with soap and water. Remove contaminated clothing and shoes; do not reuse until cleaned. If persistent irritation occurs, GET MEDICAL ATTENTION IMMEDIATELY.

Eyes: If splashed into eyes, flush with water for 15 minutes while holding eyelids open or until irritation subsides. If irritation persists, GET MEDICAL ATTENTION IMMEDIATELY.

Section V - Fire Fighting Measures

Flash Point: 109°F-TCC

Autoignition Temperature: 980°F

Lower Explosive Limit: 0.9%

Upper Explosive Limit: 12.3%

Unusual Fire and Explosion Hazards: Handle as a flammable material! Vapors may form an explosive mixture with air between the upper and lower explosive limits. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. When exposed to extreme temperature, closed containers may explode. Vapor could travel toward a source of ignition and flash back.

Extinguishing Media: Use water fog, foam, dry chemical or CO₂. Do not use a direct stream of water. Product will float and can be reignited on surface of water.

Special Firefighting Procedures: Evacuate hazard area of unprotected personnel. Wear proper protective clothing including a NIOSH approved self-contained breathing apparatus. Cool fire-exposed containers with a water mist.

Section VI - Accidental Release Measures

[Spills may need to be reported to the National Response Center (800/424-8802) **CERCLA Reportable Quantity (RQ) is 1000 pounds**]. Shut off and eliminate all ignition sources. Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent such as sand, earth or other suitable absorbent to spill area

Section VII - Handling and Storage

CAUTION: combustible! Keep away from heat, sparks and open flames. Keep containers tightly closed. Store this product away from strong oxidizing agents and in a cool, dry place with adequate ventilation.

Section VIII - Exposure Controls/Personal Protection

Respiratory Protection: None required if adequate ventilation. Only MSHA or NIOSH approved respirators should be used if concentration is above 1000 ppm.

Ventilation: Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. Use explosion-proof equipment only.

Protective Clothing: Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

Eye Protection: Use splash goggles or face shield when eye contact may occur.

Other Protective Clothing or Equipment: Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact. A safety shower is helpful

Section IX - Physical and Chemical Properties

Physical State: Liquid

pH: N/A

Melting Point/Range: N/A

Boiling Point/Range: 364-464°F
@760mm

Appearance/Color/Odor: Cloudy Colorless, aromatic odor

Solubility in Water (g/100g): Insoluble

Vapor Pressure(mmHg): ~4

Specific Gravity(Water=1): 1.06-1.07

Molecular Weight: N/A

Vapor Density(Air=1): N/A

% Volatiles by Volume: 62.3-63.3

How to detect this compound : N/A

VOC: <600 g/l or 4.38 lbs./gallon

Section X - Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions to Avoid: Avoid heat, sparks, and open flames.

Materials to Avoid: Strong oxidizing agents, concentrated nitric and sulfuric acids, and molten sulphur. Temperatures above ambient.

Hazardous Decomposition Products: Oxides of carbon, and acrylic monomer vapors.

Section XI - Toxicological Information

N/A

Section XII - Ecological Information

Do not discharge into lakes, streams, or ponds.

Section XIII - Disposal Considerations

Use non-leaking containers, seal tightly and label properly. Dispose of in accordance with applicable local, county, state and federal regulations.

Section XIV - Transport Information

DOT Proper Shipping Name: Paint
DOT Hazard Class/ I.D. No.: 3, UN1263, III

Section XV - Regulatory Information

Reportable Quantity: N/A

NFPA Rating: Health - 2; Fire - 2; Reactivity - 0

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Carcinogenicity Lists: Yes **NTP:** No **IARC Monograph:** No **OSHA Regulated:** Yes
WARNING

This product contains chemicals known to the State of California to cause cancer

Section 313 Supplier Notification: This product contains the following toxic chemical(s) subject to the reporting requirements of SARA TITLE III Section 313 of the Emergency Planning and Community Right-To Know Act of 1986 and of 40 CFR 372:

<u>CAS #</u>	<u>Chemical Name</u>	<u>% By Weight</u>
95-63-6	Pseudocumene	<1
1330-20-7	Xylene	32-34

Synonyms/Common Names: Desert Brand Masterseal High Viscosity Clear.

Chemical Family/Type: Paint

Change(s) Since Last Revision: First Issue

IMPORTANT! Read this MSDS before use or disposal of this product. Pass along the information to employees and any other persons who could be exposed to the product to be sure that they are aware of the information before use or other exposure. This MSDS has been prepared according to the OSHA Hazard Communication Standard [29 CFR 1910.1200]. The MSDS information is based on sources believed to be reliable. However, since data, safety standards, and government regulations are subject to change

and the conditions of handling and use, or misuse are beyond our control, **Hill Brothers Chemical Company** makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. Also, additional information may be necessary or helpful for specific conditions and circumstances of use. It is the user's responsibility to determine the suitability of this product and to evaluate risks prior to use, and then to exercise appropriate precautions for protection of employees and others.