

Material Safety Data Sheet

Revision Issued: 10/10/2008 Supersedes: 6/23/2000 First Issued: 8/09/1994

Section I - Chemical Product And Company Identification

Product Name: Desert Crete Texture – Pool Deck Finish

CAS Number: N/A

HBCC MSDS No. CD01300



HILL BROTHERS *Chemical Co.*

1675 NORTHMAIN STREET • ORANGE, CALIFORNIA 92867-3499
(714) 998-8800 • FAX: (714) 998-6310
<http://hillbrothers.com>

1675 No. Main Street, Orange, California 92867
Telephone No: 714-998-8800
Chemtrec: 800-424-9300



DesertBrand.com

Flooring and Sealer Products
Since 1923

Section II - Composition/Information On Ingredients

Chemical Name	CAS Number	Exposure Limits (TWAs) in Air		
		ACGIH TLV	OSHA PEL	STEL
Calcium Carbonate	1317-65-3	Inhalable Particulates: 10 mg/m ³ ; Respirable Particulates: 3 mg/m ³	Total Dust: 15 mg/m ³ ; Respirable fraction: 10 mg/m ³	N/A
Portland Cement	65997-15-1	Total Dust: 10 mg/m ³	Total Dust: 15 mg/m ³ ; Respirable Dust: 5 mg/m ³	N/A
Calcium Sulfate	7778-18-9	Total Dust: 10 mg/m	Total Dust: 15 mg/m ³ ; Respirable Dust: 5 mg/m ³	N/A
Magnesium Oxide	1309-48-4	Total Dust: 10 mg/m ³	Total Dust: 15 mg/m ³	N/A
Crystalline Silica	14808-60-7	Respirable Dust: 0.05 mg/m ³	Total Dust: 10.7 mg/m ³ ; Respirable Dust: 3.6 mg/m ³	N/A
Kaolin	1332-58-7	Respirable Dust: 2 mg/m ³	Inhalable Dust: 15 mg/m ³ ; Respirable Dust: 5 mg/m ³	N/A
VaE polymer	Proprietary	N/A:	N/A	N/A

Section III - Hazard Identification

Routes of Exposure: Desert Crete Texture-Pool Deck Finish can affect the body if it is inhaled, ingested, or comes in contact with the eyes and skin.

Summary of Acute Health Hazards

Ingestion: May cause temporary irritation to the throat, stomach, and gastrointestinal tract.

Inhalation: This product contains crystalline silica. Long-term overexposure to crystalline silica causes silicosis, a form of pulmonary fibrosis. Continued overexposure to silica can lead to cardiopulmonary impairment.

Skin: Dust or powder may irritate the skin.

Eyes: Dust or powder may irritate eye tissue.

Signs and Symptoms of Exposure: Undue breathlessness, wheezing, cough, and sputum production.

Effects of Overexposure: Crystalline silica can cause silicosis, a progressive and frequently incapacitating pneumoconiosis evident on x-ray and in pulmonary function testing, as well as in subjective respiratory complaints.

Medical Conditions Generally Aggravated by Exposure: Pulmonary function may be reduced by inhalation of respirable crystalline silica. Also lung scarring produced by such inhalation may lead to a progressive massive fibrosis of the lung which may aggravate other pulmonary conditions and diseases and which increases susceptibility to pulmonary tuberculosis. Progressive massive fibrosis may be accompanied by right heart enlargement, heart failure, and pulmonary failure. Smoking aggravates the effects of exposure.

Note to Physicians: N/A

Section IV - First Aid Measures

Ingestion: N/A

Inhalation: Remove victim to fresh air and administer artificial respiration if required. GET MEDICAL ATTENTION, if needed.

Skin: Flush skin with plenty of water. If rash develops, get medical attention.

Eyes: Immediately flush with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION, if discomfort persists.

Section V - Fire Fighting Measures

Flash Point: N/A

Autoignition Temperature: N/A

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Unusual Fire and Explosion Hazards: N/A

Extinguishing Media: N/A

Special Firefighting Procedures: Be aware of runoff from fire control methods. Do not release material to waterways, as product reacts with water and hardness within 1 to 6 hours.

Section VI - Accidental Release Measures

Use dustless methods (vacuum) and place into closable container for disposal, or flush with water. Do not dry sweep. Wear protective equipment.

Section VII - Handling and Storage

Wear thick working gloves and safety glasses. Persons not wearing protective equipment as noted in Section XVI should be restricted from areas with spills or dust accumulation. Use waste containers suitable for transportation. Avoid breakage of bagged material or spills of bulk materials.

Other Precautions: Keep from freezing, material may coagulate, minimum storage temperature is 34°F, maximum is 120°F.

Section VIII - Exposure Controls/Personal Protection

Respiratory Protection: See Section XVI.

Ventilation: Local is preferable, but mechanical is acceptable.

Protective Clothing: Protective gloves are advisable, and goggles or a face shield should be used.

Other Protective Clothing or Equipment: N/A

Work/Hygienic Practices: Wash hands thoroughly with soap and water before eating, drinking, smoking or using toilet facilities. Do NOT place food, coffee or other drinks in the area where dusting or splashing of solutions is possible.

Section IX - Physical and Chemical Properties

Physical State: Solid

pH:

Melting Point/Range: N/A

Boiling Point/Range: N/A

Appearance/Color/Odor: Solid/White/Acrylic

Solubility in Water: Minimal

Vapor Pressure(mmHg): N/A

Specific Gravity(Water=1):2.54

Molecular Weight:

Vapor Density(Air=1): N/A

% Volatiles: Negligable

Weight/Gallon (Lbs.): 21.13

Section X - Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid: Water will harden mixture. Contact with water will result in hydration and produces (caustic) calcium hydroxide.

Materials to Avoid: Acids, ammonium salts and aluminum metal. Calcium Carbonate ignites on contact with fluorine.

Hazardous Decomposition Products: Thermal oxidative decomposition of calcium carbonate can produce calcium oxide.

Section XI - Toxicological Information

Overexposure to calcium carbonate may result in irritation to eyes, skin and respiratory system. Acute ingestion may result in mild gastrointestinal distress while chronic exposure may result in hypercalcemia, alkalosis and renal impairment. Animal studies suggest that inhalation of calcium carbonate dusts may enhance susceptibility to respiratory infection.

Section XII - Ecological Information

N/A

Section XIII - Disposal Considerations

Disposal must be done in accordance with Local, State, and Federal regulations.

Section XIV - Transport Information

DOT Proper Shipping Name: N/A
DOT Hazard Class/ I.D. No.: N/A

Section XV - Regulatory Information

Reportable Quantity: N/A

NFPA Rating: Health - 2; Flammability - 0; Instability - 0

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Carcinogenicity Lists: NTP: No **IARC Monograph:** No **OSHA Regulated:** No

WARNING

This product contains crystalline silica, a chemical known to the State of California to cause cancer.

Section XVI - Other Information

Section(s) changed since last revision: II, IX

Synonyms/Common Names: N/A

Chemical Family/Type: Silica, Quartz, Portland Cement Mixture

Respiratory protection for crystalline silica minimum respiratory protection

Particulate Concentration:

5 x PEL or less: Any dust respirator.

10 x PEL or less: Any dust respirator, except single-use or quarter-mask respirator. OR Any dust respirator, except single-use or quarter-mask respirator. OR Any supplied-air respirator. OR Any self-contained breathing apparatus.

50 x PEL or less: A high efficiency particulate filter respirator with a full facepiece. OR Any supplied-air respirator with a full facepiece, helmet, or hood. OR Any self-contained breathing apparatus with a full facepiece.

500 x PEL or less: A powered air-purifying respirator with a high efficiency particulate filter. OR A Type C supplied- air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.

Greater than 500 x PEL or entry and escape from unknown concentrations:

Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. OR A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.

Abrasive Blasting: Any Type CE, supplied-air respirator with a full facepiece, hood, or helmet, operated in a positive-pressure mode. Only NIOSH-approved or MSHA-approved equipment should be used.

IMPORTANT! Read this MSDS before use or disposal of this product. Pass along the information to employees and any other persons who could be exposed to the product to be sure that they are aware of the information before use or other exposure. This MSDS has been prepared according to the OSHA Hazard Communication Standard [29 CFR 1910.1200]. The MSDS information is based on sources believed to be reliable. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, [Hill Brothers Chemical Company](#) makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. Also, additional information may be necessary or helpful for specific conditions and circumstances of use. It is the user's responsibility to determine the suitability of this product and to evaluate risks prior to use, and then to exercise appropriate precautions for protection of employees and others.