

**MATERIAL SAFETY DATA SHEET - CRITERION CORRECTING SOLUTION**

Manufacturer: **TASKEM, Inc.**  
**4639 Van Epps Road**  
**Brooklyn Heights, Ohio 44131**  
**(216) 351-1500**

NFPA Rating  
-----  
Health: 1  
Flammability: 0  
Reactivity: 0

Latest Revision Date for MSDS Information: October 7, 2005

Information on this product is on file with CHEMTREC. FOR EMERGENCY ASSISTANCE CALL 1-800-424-9300. If water pollution occurs, notify appropriate authorities.

**SECTION I - PRODUCT IDENTIFICATION**

Trade Name: CRITERION CORRECTING SOLUTION  
Product Identification Number: 32700  
General or Generic Id: Nickel Plating Bath Additive

**SECTION II - HAZARDOUS INGREDIENTS**

This product does not contain material(s) listed as toxic chemicals as defined by the requirements of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III - Section 313, nor does it contain material(s) which are listed as hazardous chemicals as defined by OSHA's Hazard Communication Standard (29 CFR 1910.1200).

**SECTION III - PHYSICAL DATA**

Vapor Density: Heavier than Air  
Solubility in Water: Complete  
Appearance and Odor: Very Light Yellow, Odorless Liquid.  
Specific Gravity: 1.018 - 1.034  
Percent Volatiles: Approx. 85%  
Evaporation Rate: Slower than Ether

**SECTION IV - FIRE AND EXPLOSION HAZARDS**

Flammability Classification (DOT): Not Flammable  
Flash Point: Does Not Apply  
Extinguishing Media: Foam, CO<sub>2</sub>, Dry Chemical, Water Fog  
Special Fire Fighting Procedures: Positive pressure, self-contained respiratory protection and protective clothing should be worn by firefighters in areas where product is stored.  
Unusual Fire & Explosion Hazards: None.

**SECTION V - HEALTH HAZARD DATA**

*Effects of Overexposure:*

Eyes: Mild irritant. Prolonged or repeated contact may cause redness and irritation.  
Skin: Mild irritant. Prolonged or repeated contact may cause irritation.  
Breathing: Inhalation of mists or liquid may be irritating to mucous membrane of the respiratory tract.  
Swallowing: Industrial chemicals are never to be taken internally. Irritating to mucous membrane.

*First Aid:*

If in Eyes: Flush with clean water for 15 minutes. Contact a Physician. Washing eyes within 1 minute after contact is essential to achieve maximum effectiveness.  
If on Skin: Immediately wash skin with soap and plenty of water. Remove contaminated clothing and do not re-use until laundered.  
If Inhaled: Remove victim to fresh air. Seek medical attention. If breathing has stopped, start artificial respiration.  
If Swallowed: Do not induce vomiting. Give large quantities of milk and/or water. Seek medical attention

NOTE: The above *Health Hazard Data* applies to contact with the product itself, not the operating solutions in which it is used, which contain dissolved nickel salts in a slightly acidic solution. In the case of contact with the operating solution, follow treatment methods applicable for exposure to this type of solution.

**MATERIAL SAFETY DATA SHEET - CRITERION CORRECTING SOLUTION**

**SECTION VI - REACTIVITY DATA**

Stability: Stable  
Conditions to Avoid: See SECTION IX.  
Incompatibility (Materials to Avoid): None Known  
Hazardous Decomposition Products: None  
Hazardous Polymerization: Will not occur

**SECTION VII - SPILL OR LEAK PROCEDURES**

*Steps to be Taken in Case of a Spill:*

Small Spill: Stop leaks. Contain spill. Flush with water to in-house treatment system for proper disposal, or cover with absorbent materials and shovel into closeable container for proper disposal.  
Large Spill: Stop leaks. Contain spill. Remove as much as possible for routine use. Flush with water to in-house treatment system for proper disposal, or cover with absorbent materials and shovel into closeable container for proper disposal.

*Waste Disposal Method:*

Small Spill: Dispose of in accordance with Federal, State, and Local regulations.  
Large Spill: After recovery, dispose of in accordance with Federal, State, and Local regulations.

NOTE: The above *Spill or Leak Information* refers to the product itself, not the operating solutions in which it is used, which contain dissolved nickel salts in a slightly acidic solution. In the case of a spill of the operating solution, treat accordingly.

**SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED**

Respiratory Protection: Use appropriate NIOSH approved respiratory equipment for dust and mists.  
Ventilation: Exhaust ventilation to maintain air contamination below TLV. Mechanical ventilation recommended.  
Protective Gloves: Rubber  
Eye Protection: Safety Glasses  
Other Protective Equipment: Rubber Apron. Safety showers and eye wash stations should be near handling areas.

**SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS**

Precautions to be Taken in Storing or Handling:

Keep containers closed when not in use. Protect from freezing. If material freezes, move to warm area and allow to thaw. Mix well prior to use to insure uniform composition of material.

Other Precautions:

Product is typically used in conjunction with dissolved nickel salts in slightly acidic solutions operated at elevated temperatures. When working with, or near, operating solutions, exercise normal cautions to be used when handling this type of solution.

**SECTION X - TRANSPORTATION AND LABELING DATA**

DOT Proper Shipping Name: Not Regulated  
DOT Proper Hazard Class: Not Regulated  
DOT ID Number: Not Regulated  
Precautionary Labels: None Required

---

**U.S. TSCA Inventory: All components are included on the U.S. TSCA Inventory.**

---

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND IS ACCURATE TO THE BEST OF THE SELLER'S KNOWLEDGE. HOWEVER, SELLER MAKES NO WARRANTY WHATSOEVER, EXPRESSED, IMPLIED, OR OF MERCHANTABILITY REGARDING THE ACCURACY OF SUCH DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SELLER ASSUMES NO RESPONSIBILITY FOR INJURY TO BUYER OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND BUYER ASSUMES ALL SUCH RISKS.

---