

010 09/09/04 DOWFROST\* HEAT TRANSFER FLUID

\*\*\*\*\*  
 PRODUCT IDENTIFICATION  
 \*\*\*\*\*

PRODUCT NAME: DOWFROST\* HEAT TRANSFER FLUID  
 MSDS#: DW23545  
 DATE ISSUED: 05/27/2004  
 SUPERSEDES: 05/09/2002  
 ISSUED BY: 009053

## MATERIAL SAFETY DATA SHEET

DOW THE DOW CHEMICAL COMPANY

Product Name: DOWFROST\* Heat Transfer Fluid / Effective Date: 05/27/2004  
 MSDS#: 1376

Dow (hereinafter, and for purposes of this MSDS only, refers to The Dow Chemical Company and to Dow Chemical Canada Inc.) encourages and expects you to read and understand the entire MSDS, as there is important information throughout the document. Dow expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

## 1.1 IDENTIFICATION

Product Name DOWFROST\* Heat Transfer Fluid

## 1.2 COMPANY IDENTIFICATION

The Dow Chemical Company  
 Midland, MI 48674

## 1.3 EMERGENCY TELEPHONE NUMBER

24-HOUR EMERGENCY TELEPHONE NUMBER: (989)636-4400.

Customer Information Number: 1-800-258-2436.

\*

or (R) Indicates a Trademark of The Dow Chemical Company.

## 2. COMPOSITION INFORMATION

Component	CAS #	Amount (%W/W )
Propylene glycol	57-55-6	> 95
Demineralized water	7732-18-5	< 5%
Dipotassium hydrogen phosphate	7758-11-4	< 5%

## 3. HAZARDS IDENTIFICATION

## 3.1 EMERGENCY OVERVIEW

Appearance Colorless

Physical State Liquid

Odor Mild

Hazards of product

NO SIGNIFICANT IMMEDIATE HAZARDS FOR EMERGENCY RESPONSE ARE KNOWN.

## 3.2 POTENTIAL HEALTH EFFECTS

## Effects of Single Acute Overexposure

Inhalation At room temperature, exposure to vapor is minimal due to low volatility. Mist may cause irritation of upper respiratory tract (nose and throat).

### Eye Contact

May cause slight temporary eye irritation. Corneal injury is unlikely.

### Skin Contact

Prolonged contact is essentially nonirritating to skin. Repeated contact may cause flaking and softening of skin.

### Skin Absorption

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Swallowing Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

### Chronic, Prolonged or Repeated Overexposure

Effects of Repeated Overexposure In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

Other Effects of Overexposure No information currently available.

See Section 11 for toxicological information and additional information about potential health effects.

## 3.3 POTENTIAL ENVIRONMENTAL EFFECTS

See Section 12 for Ecological Information.

## 4. FIRST AID PROCEDURES

### 4.1 INHALATION

Move person to fresh air; if effects occur, consult a physician.

### 4.2 EYE CONTACT

Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

### 4.3 SKIN CONTACT

Wash skin with plenty of water.

### 4.4 SWALLOWING

No emergency medical treatment necessary.

### 4.5 NOTES TO PHYSICIAN

No specific antidote.

Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES - REFER TO SECTION 9, PHYSICAL AND CHEMICAL PROPERTIES

### 5.2 EXTINGUISHING MEDIA

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

### 5.3 FIRE FIGHTING PROCEDURES

Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and

## 8.1 EXPOSURE LIMITS

Component	Exposure Limits	Skin. Form
Propylene glycol	10 mg/m <sup>3</sup> TWA8 AI HA WEEL	

In the Exposure Limits Chart above, if there is no specific qualifier (i.e., Aerosol) listed in the Form Column for a particular limit, the listed limit includes all airborne forms of the substance that can be inhaled.

A "Yes" in the Skin Column indicates a potential significant contribution to overall exposure by the cutaneous (skin) route, including mucous membranes and the eyes, either by contact with vapors or by direct skin contact with the substance. A Blank" in the Skin Column indicates that exposure by the cutaneous (skin) route is not a potential significant contributor to overall exposure.

## 8.2 PERSONAL PROTECTION

### Respiratory Protection:

Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator.

In dusty or misty atmospheres, use an approved particulate respirator.

### Ventilation:

Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

### Eye Protection:

Use safety glasses.

### Other Protective Equipment:

No precautions other than clean body-covering clothing should be needed.

Use gloves chemically resistant to this material.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance:	Colorless
Odor:	Mild
Flash Point- Closed Cup:	1020C 216 F Tag Closed Cup ASTM D 56 (Propylene glycol)

### Flammable Limits In Air:

Lower 2.6 %(V) 100 C (Propylene glycol)

Upper 12.5 %(V) 130 C (Propylene glycol)

Autoignition Temperature:	416 C 780 F
Vapor Pressure:	0.7 mmHg 20 C
Boiling Point (760 mmHg):	162 C 323 F
Vapor Density (air = 1):	2.6
Specific Gravity (H <sub>2</sub> O = 1):	1.05 20 C 120 C
Freezing Point:	<= -51 C <= -60 F
Melting Point:	Not applicable (for liquids)
Solubility in Water (by weight):	100 % 20 C
pH:	9 - 11 (5% solution in water)
Evaporation Rate (Butyl Acetate = 1):	0.07
Percent Volatiles:	98 Wt%

## 10. STABILITY AND REACTIVITY

10.1 STABILITY/INSTABILITY Thermally stable at recommended temperatures and pressures.

### Conditions to Avoid:

Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

### Incompatible Materials:

Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

**Thermal Decomposition:**

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers.

10.2 HAZARDOUS POLYMERIZATION Will not occur.

**11. TOXICOLOGICAL INFORMATION**

**ACUTE TOXICITY**

Peroral

Rat; female; LD50 = 20300 mg/kg

Percutaneous

Based on information for a similar material:

Rabbit; LD50 = > 10000 mg/kg

**DEVELOPMENTAL TOXICITY**

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals., The component(s) is/are:, Propylene glycol.

**REPRODUCTIVE TOXICITY**

Contains component(s) which did not interfere with reproduction in animal studies., Contains component(s) which did not interfere with fertility in animal studies., The component(s) is/are:, Propylene glycol.

**CHRONIC TOXICITY AND CARCINOGENICITY**

Similar formulations did not cause cancer in laboratory animals.

**GENETIC TOXICOLOGY**

In Vitro

In vitro genetic toxicity studies were negative.

In Vivo

Genetic toxicity studies in animals were negative for component(s) tested.

**SIGNIFICANT DATA WITH POSSIBLE RELEVANCE TO HUMANS**

In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

**12. ECOLOGICAL INFORMATION**

**12.1 ENVIRONMENTAL FATE**

Based largely or completely on information for: Propylene glycol. Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Degradation is expected in the atmospheric environment within minutes to hours.

**12.2 ECOTOXICITY**

Based largely or completely on information for:; Propylene glycol., Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50 >100 mg/L in the most sensitive species tested).

**12.3 FURTHER INFORMATION**

Based largely or completely on information for: Propylene glycol. Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Potential for mobility in soil is very high (Koc between 0 and 50).

**13. DISPOSAL CONSIDERATIONS**

**13.1 DISPOSAL**

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different

locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. DOW HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION 2 (Composition/ Information on Ingredients). FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

#### 14. TRANSPORT INFORMATION

##### 14.1 U.S. D.O.T.

NON-BULK

Proper Shipping Name : NOT REGULATED

BULK

Proper Shipping Name : NOT REGULATED

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

#### 15. REGULATORY INFORMATION

##### 15.1 FEDERAL/NATIONAL

OSHA HAZARD COMMUNICATION STANDARD

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTION 313

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTION 302

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.  
SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTIONS 311 AND 312

Delayed (Chronic) Health Hazard : No  
Fire Hazard : No  
Immediate (Acute) Health Hazard : No  
Reactive Hazard : No  
Sudden Release of Pressure Hazard : No

##### TOXIC SUBSTANCES CONTROL ACT (TSCA)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

##### CEPA - DOMESTIC SUBSTANCES LIST (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS)

The components of this product are on the EINECS inventory or are exempt from EINECS inventory requirements.

#### 15.2 STATE/LOCAL

PENNSYLVANIA (WORKER AND COMMUNITY RIGHT-TO-KNOW ACT): PENNSYLVANIA HAZARDOUS SUBSTANCES LIST AND/OR PENNSYLVANIA ENVIRONMENTAL HAZARDOUS SUBSTANCE LIST:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Component	CAS #	Amount
Propylene glycol	57-55-6	96.0000

PENNSYLVANIA (WORKER AND COMMUNITY RIGHT-TO-KNOW ACT): PENNSYLVANIA SPECIAL HAZARDOUS SUBSTANCES LIST:

To the best of our knowledge this product does not contain chemicals at levels which require reporting under this statute.

CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

CALIFORNIA SCAQMD RULE 443.1 (SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT RULE 443.1, LABELING OF MATERIALS CONTAINING ORGANIC SOLVENTS)

VOC: Vapor pressure 0.66 mmHg @ 20 C

1002 g/l VOC

1030 g/l less water and less exempted solvents

This section provides selected regulatory information on this product including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

#### 16. OTHER INFORMATION

##### 16.1 ADDITIONAL INFORMATION

Additional information on this and other Dow products may be obtained by visiting our web page at [www.dow.com](http://www.dow.com).

Additional information on this product may be obtained by calling Dow's Customer Information Group at 1-800-258-2436 (U.S.) or 1-800-331-6451 (Canada).

##### 16.2 HAZARD RATING SYSTEM

NFPA ratings for this product are: H - 0      F - 1      R - 0

These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

##### 16.3 RECOMMENDED USES AND RESTRICTIONS

Intended as a heat transfer fluid for closed-loop systems.

Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group at 1-800-258-2436 (U.S.) or 1-800-331-6451 (Canada) for more information.

##### 16.4 REVISION

Version: 5.0

Revision: 05/27/2004

Most recent revision(s) are noted by the bold, double bars in left-hand

margin throughout this document.

16.5 LEGEND

Bacterial/NA Non Acclimated Bacteria  
F Fire  
H Health  
IHG Industrial Hygiene Guideline  
N/A Not available  
NFPA National Fire Protection Association  
O Oxidizer  
R Reactivity  
TS Trade secret  
VOLNOL Volume/Volume  
W Water Reactive  
W/W Weight/Weight

----- FOR ADDITIONAL INFORMATION -----

CONTACT: MSDS COORDINATOR UNIVAR USA INC.  
DURING BUSINESS HOURS, PACIFIC TIME (425) 889-3400

----- NOTICE -----

\*\*\*\*\* UNIVAR USA INC ("UNIVAR") EXPRESSLY DISCLAIMS

-----  
ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

-----  
PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED HEREIN,

-----  
AND SHALL UNDER NO CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL  
DAMAGES. \*\*

-----  
DO NOT USE INGREDIENT INFORMATION AND/OR INGREDIENT PERCENTAGES IN THIS MSDS  
AS A PRODUCT SPECIFICATION. FOR PRODUCT SPECIFICATION INFORMATION REFER TO A  
PRODUCT SPECIFICATION SHEET AND/OR A CERTIFICATE OF ANALYSIS. THESE CAN BE  
OBTAINED FROM YOUR LOCAL UNIVAR SALES OFFICE.

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE  
MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS  
BELIEVED TO BE ACCURATE, UNIVAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR  
SUFFICIENCY. CONDITIONS OF USE ARE BEYOND UNIVARS CONTROL AND THEREFORE USERS  
ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO  
DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY  
ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM  
THE PUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN.  
THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT  
RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER  
PROCESS.

\* \* \* E N D O F M S D S \* \* \*